
URBAN STREET DESIGN AND PEDESTRIAN SAFETY

Dr. Shubhajit Sadhukhan

Associate Professor

Department of Architecture and Planning

Indian Institute of Technology Roorkee

Roorkee, Uttarakhand, India

Abstract

Pedestrian safety is a defining measure of urban street quality because streets are not only movement corridors but also public spaces used for walking, waiting, trading, social interaction, access to transit, and everyday mobility. Yet pedestrians remain vulnerable where street design prioritises vehicle speed, long crossing distances, discontinuous footpaths, poor visibility, and inconsistent control of traffic at conflict points. This paper examines the relationship between urban street design and pedestrian safety through a structured review and conceptual analysis of planning, traffic-engineering, public-health, and road-safety literature.

The study considers how street geometry, operating speed, sidewalk continuity, crossing design, intersection treatment, lighting, land-use intensity, parking management, public-transport access, universal-design features, and traffic-calming measures influence pedestrian exposure and injury risk. Particular attention is given to the distinction between a street that is technically walkable and a street that is genuinely safe, legible, comfortable, and accessible for children, older adults, persons with disabilities, and people making short daily trips.

The review indicates that pedestrian safety improves when streets use a safe-system approach: vehicle speeds are managed, conflict points are simplified, crossing distances are reduced, sidewalks are continuous and unobstructed, and street environments support predictable interaction among all road users. Raised crossings, refuge islands, curb extensions, compact intersections, protected waiting areas, street lighting, visible markings, and transit-oriented pedestrian networks can reduce risk when they are designed as part of a connected street system rather than as isolated interventions.

The paper concludes that pedestrian safety should be embedded in urban street design from the earliest planning stage. Effective policy must combine design standards, maintenance, enforcement, speed management, data-led safety audits, community participation, and equity-sensitive implementation. The findings provide a practical framework for planners, municipal authorities, engineers, researchers, and decision-makers seeking to make everyday urban movement safer and more inclusive.

Keywords: Urban Street Design, Pedestrian Safety, Walkability, Traffic Calming, Safe Crossings, Sidewalks, Road Safety, Complete Streets, Universal Design, Sustainable Mobility

1. INTRODUCTION

Urban streets structure daily life. They provide access to homes, schools, workplaces, markets, health facilities, public transport, and civic spaces. For pedestrians, the street environment determines not only whether a destination can be reached on foot but also whether that journey can be made safely, comfortably, and with dignity. In rapidly urbanising cities, walking remains a fundamental travel mode even where motorisation is increasing. However, street systems frequently continue to be designed around vehicle throughput rather than the safety of people moving at walking speed.

Pedestrian injuries and fatalities are strongly connected with the physical and operational features of streets. Wide carriageways, high

design speeds, multiple turning movements, long signal cycles, informal parking, missing footpaths, poor lighting, and inadequate crossings increase the exposure of pedestrians to conflict with motor vehicles. The risk is not distributed equally. Children, older persons, persons with disabilities, low-income workers, school students, and transit users are more likely to rely on walking and are often most affected by unsafe street conditions.

Urban street design influences safety through several pathways. Geometry shapes the speed at which drivers feel comfortable travelling. Intersection layout determines the number and complexity of conflict points. Sidewalk quality determines whether pedestrians remain separated from moving vehicles. Crossing facilities determine how long pedestrians are

exposed in the carriageway. Land-use patterns and public-transport stops affect where people choose or need to cross. Lighting, signage, visibility, and maintenance affect whether users can interpret the environment and make safe decisions.

Traditional approaches to pedestrian safety often focus on individual behaviour, such as encouraging pedestrians to use crossings or drivers to obey traffic rules. These measures are necessary but incomplete. A safe-system perspective recognises that human error is inevitable and that streets should therefore be designed so that mistakes do not result in severe injury or death. This means reducing kinetic energy through speed management, providing forgiving road environments, and protecting the most vulnerable road users at predictable conflict points.

The objective of this paper is to examine how urban street design affects pedestrian safety and to identify practical design measures that can reduce risk while strengthening walkability and inclusive access. The paper reviews major theoretical and empirical contributions, identifies the object of study, describes a review-based methodology, analyses key design mechanisms, and discusses policy implications for safer urban mobility.

2. LITERATURE REVIEW

The literature on pedestrian safety combines insights from traffic engineering, urban design, transport planning, public health, behavioural research, and road-safety policy. A common conclusion is that pedestrian risk is not produced by a single factor. It emerges from the interaction of vehicle speed, traffic volume, street geometry, crossing opportunity, land use, visibility, road-user behaviour, and the quality of pedestrian infrastructure. Urban-design scholarship further argues that street form influences both the likelihood of walking and the conditions under which walking occurs.

TABLE 1: SUMMARY OF KEY LITERATURE ON URBAN STREET DESIGN AND PEDESTRIAN SAFETY

S. No.	Author(s) / Year	Design or Safety Focus	Study Context	Key Contribution
1	Jacobs (1993)	Traffic safety and street networks	Urban road networks	Shows that lower vehicle exposure and more connected, slower street networks can improve safety outcomes.

A central theme is the relationship between vehicle speed and injury severity. When motor vehicles travel faster, drivers have less time to perceive and react to pedestrians, braking distances increase, and the physical consequences of a collision become more severe. Street elements such as narrow lanes, raised intersections, frequent crossings, street trees placed appropriately, curb extensions, and compact junctions can communicate a lower-speed environment and support speed management. The design of the street therefore acts as a continuous signal about expected driver behaviour.

Another major theme is the importance of crossing design. Pedestrians are exposed to greatest risk when they must cross wide, multi-lane roads without a protected or clearly marked route. Research on engineering countermeasures highlights the value of median refuges, curb extensions, pedestrian signals, raised crosswalks, adequate waiting areas, improved visibility, and controlled turning movements. However, the suitability of each measure depends on traffic speed, volume, road width, pedestrian demand, surrounding land use, and the presence of transit stops or schools.

The literature also identifies the role of network continuity and social context. A high-quality crossing is less useful when sidewalks do not connect to it, when vendors or parked vehicles block the pedestrian path, or when street lighting and surveillance are poor. Public-space approaches emphasise that a safe street is not only a roadway with safety hardware; it is a legible and inclusive place in which movement, access, and activity can coexist. Recent safe-system guidance therefore promotes a combination of speed management, safer infrastructure, vehicle safety, post-crash response, and institutional responsibility.

2	Dumbaugh (2005)	Street design and crash patterns	Urban arterial roads	Links conventional road design choices with crash risk and highlights the safety value of context-sensitive design.
3	Ewing & Dumbaugh (2009)	Built environment and safety	Planning and transport research	Reviews how roadway design, land use, and urban form influence traffic safety.
4	Southworth (2005)	Walkable-city design	Urban design	Explains how continuous pedestrian networks, comfort, and connectivity support walking.
5	Jacobsen (2003)	Safety in numbers	Walking and cycling exposure	Suggests that higher levels of walking can be associated with lower individual risk under supportive conditions.
6	Retting et al. (2003)	Engineering countermeasures	Urban pedestrian safety	Reviews traffic-engineering measures that can reduce pedestrian crashes and injuries.
7	Gårder (2004)	Crosswalk treatment and speed	Urban crossings	Finds that crossing safety depends on speed, vehicle flow, pedestrian volume, and site design.
8	Marshall & Garrick (2011)	Street-network design	US cities	Connects network patterns, connectivity, and roadway design with safety performance.
9	Rosen & Sander (2009)	Impact speed and fatality risk	Pedestrian collisions	Demonstrates the steep increase in fatality risk as vehicle impact speed rises.
10	NACTO (2013)	Urban street design guidance	City streets	Provides practical design tools for safer crossings, lane management, and pedestrian priority.
11	OECD/ITF (2018)	Safe-system urban policy	City road safety	Frames road safety as a shared-system responsibility with emphasis on vulnerable road users.
12	WHO (2023)	Global road safety	International evidence	Reinforces the importance of safer speeds, infrastructure, legislation, and implementation capacity.

3. OBJECT OF STUDY

The object of this study is urban street design viewed through the lens of pedestrian safety. The analysis focuses on the physical, operational, and perceptual conditions that shape pedestrian exposure to traffic risk during everyday trips. It considers both the immediate location of a pedestrian interaction, such as a crossing or intersection, and the wider street-network conditions that influence speed, route choice, traffic volume, and access to destinations. The study examines how design factors interact with user characteristics and urban conditions. Principal design factors include carriageway width, lane configuration, operating speed, sidewalk width and continuity, crossing distance, median design, corner radius, intersection control, lighting, parking layout, transit-stop placement, surface quality, and accessibility features. User-related considerations include age, mobility

limitations, trip purpose, confidence, walking speed, and exposure to congestion or informal street activity.

In addition, the study considers institutional and implementation factors that influence whether safety-oriented designs are sustained over time. These include maintenance, enforcement, street-vending management, construction-zone protection, road-safety audits, crash-data systems, public participation, and coordination among planning, engineering, police, health, and transport agencies. The aim is to develop a balanced framework that treats pedestrian safety as a design, governance, and equity issue rather than a narrow traffic-control problem.

KEY POINTS OF OBJECT OF STUDY

- To examine how street geometry and operating speed influence the severity and likelihood of pedestrian conflicts.

- To analyse the role of sidewalks, crossings, medians, curb extensions, and intersection design in reducing pedestrian exposure.
- To assess how lighting, markings, visibility, and legibility affect pedestrian confidence and safe decision-making.
- To investigate the needs of children, older adults, persons with disabilities, transit users, and other vulnerable pedestrians.
- To consider how parking, loading, street vending, construction activity, and maintenance affect the usable pedestrian realm.
- To compare isolated safety treatments with corridor and network-level approaches to pedestrian protection.
- To study how land-use intensity, public-transport access, and activity patterns influence crossing demand and route choice.
- To evaluate the role of traffic calming, safe speeds, and street redesign in preventing severe injuries.
- To identify governance, data, enforcement, and participation mechanisms that support durable safety improvements.
- To develop a conceptual framework for inclusive, safe, and walkable urban streets.

TABLE 2: OBJECT OF STUDY FRAMEWORK

S. No.	Study Component	Description	Purpose
1	Pedestrian Exposure	Walking routes, crossing frequency, waiting time, and proximity to moving traffic	Understand where and when pedestrians face traffic conflict
2	Street Geometry	Carriageway width, lane count, corner radius, medians, and alignment	Assess how physical form influences speed and crossing distance
3	Pedestrian Infrastructure	Sidewalks, ramps, tactile surfaces, crossings, refuge islands, and lighting	Evaluate protection, continuity, and universal accessibility
4	Speed Environment	Design speed, operating speed, calming measures, and enforcement	Identify interventions that reduce impact severity
5	Intersection and Crossing Design	Signals, markings, turning movements, phasing, visibility, and waiting areas	Examine the highest-risk conflict locations
6	Land Use and Activity	Schools, markets, transit stops, mixed use, vending, and parking demand	Recognise pedestrian demand created by surrounding urban activity
7	Governance and Maintenance	Audits, repairs, enforcement, data systems, and agency coordination	Assess whether safety features remain effective over time
8	Safety and Inclusion Outcomes	Crash reduction, comfort, access, confidence, and equitable mobility	Connect design quality with public safety and social participation

4. RESEARCH METHODOLOGY

This paper uses an explanatory and integrative review design. Rather than collecting a new primary survey, it synthesises foundational theories, peer-reviewed empirical studies, urban-design guidance, road-safety reports, and professional practice documents related to pedestrian risk and street design. The approach

is appropriate because the research question concerns the mechanisms through which design decisions shape safety across diverse urban settings, user groups, and transport systems.

The review is organised around five analytical domains: street geometry and speed; pedestrian-network continuity; crossing and

intersection design; visibility, accessibility, and public-space quality; and institutional delivery through audits, maintenance, and governance. Sources are considered for the design problem addressed, the setting studied, the safety mechanism identified, and the implications for planning and implementation. The analysis gives special attention to measures that reduce serious-injury risk rather than merely improving visual appearance or perceived walkability.

To preserve conceptual clarity, the paper distinguishes between pedestrian activity, crash frequency, injury severity, perceived safety, and accessibility. A street may attract more walkers because it is well connected, yet still present risks if motor-vehicle speed and crossing design are poorly managed. Likewise, a reduction in recorded crashes may reflect lower pedestrian activity or under-reporting rather than an improved environment. Interventions are therefore discussed in relation to exposure, severity, equity, and long-term usability.

4.1 RESEARCH DESIGN

- Study Type: Explanatory and literature-based research.
- Approach: Integrative review and conceptual synthesis.
- Unit of Analysis: Urban street segments, intersections, crossings, and pedestrian travel environments.
- Primary Design Domains: Speed management, sidewalks, crossings, intersection geometry, lighting, and universal design.
- Urban Context Variables: Land use, traffic volume, public transport, parking, pedestrian demand, and maintenance conditions.
- Outcome Variables: Pedestrian exposure, crash risk, injury severity, comfort, accessibility, and perceived safety.
- Ethical Position: No personal or human-subject data were collected for this study.

4.2 METHODOLOGICAL STEPS

- Step 1: Define pedestrian safety as a street-system outcome involving design, operation, maintenance, and user needs.


- Step 2: Identify major design variables associated with pedestrian exposure, conflicts, and injury severity.
- Step 3: Review evidence from urban streets, intersections, school zones, transit corridors, and mixed-use activity areas.
- Step 4: Classify interventions by mechanism, such as speed reduction, separation, visibility, crossing support, or accessibility.
- Step 5: Compare reported outcomes related to crashes, injury severity, yielding behaviour, walkability, and user comfort.
- Step 6: Interpret findings in relation to vulnerable-user needs, traffic conditions, and local implementation capacity.
- Step 7: Identify limitations, including variation in data quality, design standards, and urban context across cities.
- Step 8: Develop planning and design implications that integrate safety, inclusion, mobility, and public-space quality.

5. DATA ANALYSIS

The data analysis is based on qualitative synthesis of the reviewed literature and design guidance. The evidence is interpreted by tracing how a street-design feature affects the probability that pedestrians will encounter a conflict, how long they remain exposed to traffic, whether drivers can perceive and yield to them, and how severe a crash is likely to be if it occurs. The analysis does not report newly collected crash observations; instead, it consolidates recurrent patterns in the relationship between street form and pedestrian safety.

Across the reviewed studies, the consistent conclusion is that pedestrian safety is not determined by user caution alone. People benefit when the desired action is easy to understand, when crossings are located where people actually need them, when motor speeds are compatible with pedestrian survival, and when footpaths are continuous and accessible. The following sections organise the analysis around four design mechanisms that are especially influential in urban pedestrian safety.

Graph 1. Conceptual Priority of Street Design Measures for Pedestrian Safety



Graph 1. Conceptual Priority of Street Design Measures for Pedestrian Safety

Note: The graph presents a conceptual synthesis of recurring priorities in the reviewed design and safety literature. It is not a statistical estimate from a single primary dataset.

5.1 STREET GEOMETRY, SPEED, AND CONFLICT SEVERITY

Vehicle speed is one of the most consequential factors in pedestrian safety because it affects both crash likelihood and injury severity. Wide lanes, long straight sections, large corner radii, and roadway designs that communicate high-speed movement can encourage drivers to travel faster than is appropriate for active urban environments. Even when a posted speed limit is low, street geometry may communicate a different expectation to drivers. A pedestrian-safe street therefore requires consistency between its intended speed, its physical form, and its surrounding land use.

Traffic-calming measures work by altering the operating environment rather than relying only on signs. Raised tables, speed humps, chicanes, compact intersections, narrowed lane widths, curb extensions, gateway treatments, and streetscape features can reduce speed and increase driver attention. These measures should be selected carefully. A treatment that works on a residential street may be unsuitable on a bus corridor or emergency route unless it is designed to accommodate vehicle operations while still maintaining a safe pedestrian speed environment.

KEY OBSERVATION:

- Safer pedestrian environments depend on operating speeds that are compatible with human survival and reaction time.
- Street geometry can either reinforce or undermine formal speed-limit rules.
- Speed-management measures are strongest when applied consistently across a corridor or neighbourhood rather than at isolated points.

5.2 SIDEWALK CONTINUITY, ACCESSIBILITY, AND EVERYDAY WALKING

Sidewalks are the basic protective layer of the pedestrian network. A usable sidewalk must be continuous, adequately wide, well maintained, free of unnecessary obstructions, and connected to crossings, transit stops, building entrances, and side streets. Discontinuous paths force pedestrians into the carriageway, while broken surfaces, open drains, poorly designed ramps, and encroachments create particular barriers for wheelchair users, older adults, children, persons carrying goods, and people with visual impairments.

Universal design strengthens safety because it improves the predictability of the walking environment. Tactile guidance, kerb ramps, appropriate gradients, non-slip surfaces,

audible signals where justified, resting opportunities, shade, and accessible waiting areas allow a broader range of users to navigate the street. These elements should not be treated as optional add-ons. When incorporated from the start, they reinforce a street system that is safer, more comfortable, and more inclusive for everyone.

KEY OBSERVATION:

- A crossing cannot be considered safe if pedestrians cannot reach it through a continuous and accessible footpath.
- Maintenance, drainage, utility work, parking, and street-vending management affect the real usable width of a sidewalk.
- Universal-design features improve safety by reducing uncertainty and physical barriers for a wide range of users.

5.3 CROSSINGS, INTERSECTIONS, AND TURNING MOVEMENTS

Crossings and intersections are concentrated conflict zones because they bring pedestrians, through vehicles, turning vehicles, cyclists, transit users, and curbside activity into close proximity. The safety challenge increases where streets are wide, turning radii are large, signal phases are short, pedestrian waiting areas are inadequate, or vehicles are permitted to turn at speed. Pedestrian design should therefore start by identifying desire lines: the routes people naturally use to reach schools, markets, transit stops, parks, and building entrances.

Curb extensions shorten crossing distance and improve visibility by bringing pedestrians closer to the edge of moving traffic. Refuge islands reduce exposure by allowing crossings to be completed in two stages. Raised crossings and compact corner design can slow turning vehicles. Signal timing, leading pedestrian intervals, accessible push buttons, visible markings, and protected waiting spaces can further improve clarity. However, marked crossings alone may be insufficient on wide or fast roads if they are not supported by speed management and suitable control measures.

KEY OBSERVATION:

- Pedestrian safety depends on matching crossing treatment to speed, width, volume, pedestrian demand, and surrounding activity.

- Reducing turning speed is a central intersection-safety objective, not merely a traffic-flow consideration.
- Pedestrian desire lines should inform crossing location; otherwise, people may be forced to make unsafe informal crossings.

5.4 VISIBILITY, ACTIVITY, AND EQUITABLE STREET MANAGEMENT

Visibility is a combined outcome of lighting, sight distance, street activity, parking management, signage, landscaping, building edges, and the location of loading or vending. Poor visibility can prevent drivers from seeing a pedestrian in time and can also reduce a pedestrian's sense of personal security. Street lighting should illuminate footpaths, crossings, waiting areas, and transit stops rather than concentrating only on the carriageway. At the same time, signs, utility boxes, hoardings, and parked vehicles should not obstruct the visual relationship between pedestrians and drivers. Street activity must be managed with an equity-sensitive approach. Markets, vendors, informal employment, public transport, and small businesses generate walking demand and contribute to active streets. Removing activity without providing alternatives may reduce livelihoods while failing to solve the underlying design problem. More durable solutions provide clear pedestrian movement zones, organised loading areas, designated vending spaces where appropriate, and safe transit access. The objective is not to eliminate urban activity but to design a street where activity and movement can coexist safely.

KEY OBSERVATION:

- Pedestrian safety includes both traffic safety and the ability to use streets without avoidable fear or obstruction.
- Lighting, visibility, and clear curbside management are especially important around transit stops, schools, markets, and mixed-use streets.
- Equitable safety programmes should protect pedestrians while recognising the mobility and livelihood functions of public streets.

6. DISCUSSION

The reviewed literature demonstrates that pedestrian safety is jointly shaped by urban design, traffic operation, user behaviour, and institutional capacity. Conventional traffic

engineering remains important for signal timing, capacity analysis, and intersection control. However, a pedestrian-centred approach adds a wider question: does the street allow people to move safely and independently across age, gender, income, and ability? This question cannot be answered only by counting vehicle lanes or measuring delay for motor traffic.

Street design can either reduce or amplify the consequences of human error. A pedestrian may misjudge a gap, a driver may be distracted, a child may step unexpectedly into the road, or a person with limited mobility may need more time to cross. A safe system acknowledges these realities and provides lower speeds, shorter crossings, forgiving geometry, clear information, and physical protection. The most defensible interventions are those that reduce severe-injury risk even when every road user does not behave perfectly.

The discussion also highlights the need to evaluate pedestrian interventions carefully. A new footpath should be assessed not only for its construction quality but also for continuity, shade, drainage, access to properties, and protection during utility work. A new crossing should be assessed for driver yielding, signal timing, lighting, accessibility, and whether it corresponds to observed pedestrian demand. Road-safety audits and post-implementation reviews can identify design gaps before they become routine hazards.

For municipal authorities, the practical implication is to integrate pedestrian safety into every street project, including resurfacing, drainage, parking management, transit improvements, redevelopment, and smart-city works. Safe pedestrian design is not necessarily a separate high-cost programme. Many improvements can be delivered when routine projects use clear design standards, coordinate agencies, involve users, and protect walking routes during construction. At the same time, corridor redesign and network-level investment are needed for locations where existing conditions create persistent severe risk.

8. REFERENCES

1. American Association of State Highway and Transportation Officials. (2018). Guide for the planning, design, and operation of pedestrian facilities. AASHTO.

Equity should remain central. People who walk because they have limited access to private vehicles should not receive lower-quality infrastructure. Streets around low-income neighbourhoods, schools, health centres, public transport stops, markets, and informal settlements often have high pedestrian demand but inadequate protection. Prioritising these locations can produce substantial public-safety and social-inclusion benefits.

7. CONCLUSION

This paper examined urban street design through the framework of pedestrian safety. The analysis shows that pedestrian risk is influenced not only by individual behaviour and traffic rules but also by vehicle speed, street geometry, sidewalk continuity, crossing design, intersection treatment, lighting, accessibility, curbside activity, and the quality of public-space management. These factors explain why some streets support safe everyday walking while others expose pedestrians to recurring risk.

The evidence reviewed in this paper indicates that speed management, continuous sidewalks, compact intersections, protected crossings, curb extensions, refuge islands, clear markings, adequate lighting, accessible design, and well-managed curbside zones can make pedestrian travel safer and more usable. Their role is not simply to add visual features to a street but to reduce exposure, improve predictability, and prevent severe outcomes when errors occur. Well-designed interventions must remain context-sensitive, maintainable, and aligned with the actual movement patterns of people.

The paper concludes that pedestrian safety should be a core performance objective for urban streets. Effective implementation requires integrated planning, design standards, road-safety audits, maintenance, public participation, enforcement, reliable crash and exposure data, and particular attention to vulnerable users. Future research should examine the long-term safety, access, health, equity, and economic effects of pedestrian-focused street redesign across diverse Indian and international urban contexts.

2. Buehler, R., & Pucher, J. (2021). The growing importance of walking and cycling in urban transportation. In Routledge Handbook of Transport in Asia. Routledge.
3. Clifton, K. J., Burnier, C. V., & Akar, G. (2009). Severity of injury resulting from pedestrian-vehicle crashes: What can we learn from examining the built environment? *Transportation Research Part D: Transport and Environment*, 14(6), 425-436.
4. Department for Transport. (2007). *Manual for Streets*. Thomas Telford.
5. Dumbaugh, E. (2005). Safe streets, livable streets. *Journal of the American Planning Association*, 71(3), 283-300.
6. Elvik, R. (2000). Which are the relevant costs and benefits of road safety measures designed for pedestrians and cyclists? *Accident Analysis & Prevention*, 32(1), 37-45.
7. Ewing, R., & Cervero, R. (2010). Travel and the built environment: A meta-analysis. *Journal of the American Planning Association*, 76(3), 265-294.
8. Ewing, R., & Dumbaugh, E. (2009). The built environment and traffic safety: A review of empirical evidence. *Journal of Planning Literature*, 23(4), 347-367.
9. Federal Highway Administration. (2022). *Safe system approach for pedestrians and bicyclists*. U.S. Department of Transportation.
10. Fitzpatrick, K., Brewer, M., & Turner, S. (2006). Another look at pedestrian and driver compliance at marked crosswalks on unsignalized roadways. *Transportation Research Record*, 1982(1), 46-54.
11. Gårder, P. E. (2004). The impact of speed and other variables on pedestrian safety in Maine. *Accident Analysis & Prevention*, 36(4), 533-542.
12. Gehl, J. (2010). *Cities for people*. Island Press.
13. Global Designing Cities Initiative. (2016). *Global street design guide*. Island Press.
14. Jacobs, A. B. (1993). *Great streets*. MIT Press.
15. Jacobsen, P. L. (2003). Safety in numbers: More walkers and bicyclists, safer walking and bicycling. *Injury Prevention*, 9(3), 205-209.
16. Litman, T. (2021). *Evaluating complete streets: The value of designing roads for diverse modes, users and activities*. Victoria Transport Policy Institute.
17. Marshall, W. E., & Garrick, N. W. (2011). Does street network design affect traffic safety? *Accident Analysis & Prevention*, 43(3), 769-781.
18. National Association of City Transportation Officials. (2013). *Urban street design guide*. NACTO.
19. National Association of City Transportation Officials. (2016). *Global street design guide*. Island Press.
20. OECD/International Transport Forum. (2018). *Safer city streets: Global benchmarking for urban road safety*. OECD Publishing.
21. Pucher, J., & Buehler, R. (2010). Walking and cycling for healthy cities. *Built Environment*, 36(4), 391-414.
22. Retting, R. A., Ferguson, S. A., & McCartt, A. T. (2003). A review of evidence-based traffic engineering measures designed to reduce pedestrian-motor vehicle crashes. *American Journal of Public Health*, 93(9), 1456-1463.
23. Rosen, E., & Sander, U. (2009). Pedestrian fatality risk as a function of car impact speed. *Accident Analysis & Prevention*, 41(3), 536-542.
24. Southworth, M. (2005). Designing the walkable city. *Journal of Urban Planning and Development*, 131(4), 246-257.
25. Transport Research Board. (2010). *Highway Capacity Manual 2010*. National Academies Press.
26. United Nations Human Settlements Programme. (2013). *Streets as public spaces and drivers of urban prosperity*. UN-Habitat.
27. World Health Organization. (2023). *Global status report on road safety 2023*. WHO.
28. Zegeer, C. V., Sandt, L. S., & Scully, M. C. (2013). *How to develop a pedestrian safety action plan*. Federal Highway Administration.
29. Zegeer, C. V., Stewart, J. R., Huang, H., & Lagerwey, P. (2002). Safety effects of marked versus unmarked crosswalks at uncontrolled locations. *Transportation Research Record*, 1773(1), 56-68.